



P/O 712839-8702.

DIC Compounds (Malaysia) Sdn. Bhd.

(171369-U)

Wholly owned by DIC Corporation

Plot 481, Lorong Perusahaan Baru 2,

Kawasan Perindustrian Perai, 13600 Perai, Penang, Malaysia.

Tel: (04) 390 2311 Fax: (04) 390 0124 / 398 6917

Website: www.dcm-dic.com.my



RR. NO. : DO/05/3005

CERTIFICATE OF QUALITY ANALYSIS

It is hereby certified that the product described below is manufactured by
DIC Compounds (Malaysia) Sdn. Bhd.

Production Description : DIC-PPS FZ-1140-D5

Lot No. : PE201U2H6CN

Quantity. : 10 MT

Issue Date : 04-06-2012


Analytical Properties :

| ASH CONTENT 39 ~ 43 (%) | TENSILE STRENGTH > 167 (MPa) | IZOD (Notched) > 69 (J/m) | IZOD (Un-Notched) > 392 (J/m) | SPIRAL FLOW VALUE 40 ~ 50 (cm) |
|----------------------------------|---------------------------------------|------------------------------------|--|---|
| 42.7 | 199 | 101 | 652 | 45 |

Remarks :
(i) Testing condition for Ash Content is 815°C, 3 hours.
(ii) Testing condition for Tensile Stren 1) Testing Speed : 5mm/min.
2) Gage Length : 64mm.
(iii) Testing condition for Izod, 0.325cm with notched and without notched (un-notched).
(iv) Testing condition for Spiral Flow Value is 330°C.

The above is a summary of test results obtained from production samples.

PASSED BY :


H.L. ONG
ASSISTANT MANAGER
Q.A. DEPT.

CONFIRMED BY :


HIDEKI UCHIMI
FACTORY DIRECTOR